

PVC insulated, PVC sheathed, telephone cable

Application:

- For internal connection of telephone systems and other communication equipments.

Standard:

-British Telecom CW1308

Construction:

- Solid tinned annealed copper conductor.
- Polyester tape & nylon binder.
- PVC insulation, type TI 1.
- PVC sheath, type TM 1.

General specification:

- Working temperature: Max. 70 °C.

Cable code Acc. to CW1308	Number of pairs	conductor diameter	Insulation thickness	Sheath thickness	Mean overall diameter	Weight Approx.
		mm	mm	mm	mm	kg/km
2402	2	0.4	0.2	0.5	3.6	14
2403	3	0.4	0.2	0.6	4.4	21
2404	4	0.4	0.2	0.6	4.9	26
2406	6	0.4	0.2	0.7	5.9	38
2410	10	0.4	0.2	0.7	6.1	52
2412	12	0.4	0.2	0.8	6.8	64
2420	20	0.4	0.2	0.8	8.3	97
2503	3	0.5	0.2	0.7	5.0	29
2504	4	0.5	0.2	0.7	5.5	36
2506	6	0.5	0.2	0.7	6.5	49
2510	10	0.5	0.2	0.7	6.7	69
2512	12	0.5	0.2	0.8	7.4	84
2515	15	0.5	0.2	0.8	8.1	102
2520	20	0.5	0.2	0.9	9.3	135